



PRODUCT DESCRIPTION

This compact, high-efficiency LED spotlight delivers precise, focused illumination for architectural and landscape applications. Featuring a durable, weather-resistant housing and adjustable mounting, it ensures optimal light distribution and reliable performance in diverse outdoor environments. Ideal for accentuating features and creating impactful lighting designs with energy efficiency.

LED

IP65

IK06



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	1pc High Power LEDs
Average LED Life:	80% after 50000hrs
Color Temperature:	22000K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	84lm / 178lm

OPTICAL FEATURES

Beam Angle:	5° / 15° / 30° / 60°
Accessories:	Asymmetric Snoot / Honey comb / Spike / Rod with Spike/ Tree Strap / Pole Mounted Hoop, Base (upon request)

ELECTRICAL FEATURES

Power:	1W / 3W
Voltage:	DC 24V / AC 220V
Control Protocol:	On-Off / DMX / Dali / 1-10V / Phase / PWM

MECHANICAL FEATURES

Dimensions:	Φ35mm x H64mm x L89mm
Housing Material:	Aluminum Housing / Tempered Glass / SS304 Mounted Bracket
Finish:	Black / White / Grey / Customized
Mounting Type:	Surface Mounted (Ground / Wall)

GENERAL FEATURES

Ingress Protection:	IP 65
Operating Temp:	-35°C to 50°C
Impact Resistance:	IK 06
Insulation Class:	Class I / Class III
Power Cable:	Include 1m Neoprene Cable (customizable lengths)

DIMENSION DRAWING

