



PRODUCT DESCRIPTION

This compact, high-efficiency LED projector light delivers precise, focused illumination for architectural and landscape applications. Featuring a durable, weather-resistant housing and adjustable mounting, it ensures optimal light distribution and reliable performance in diverse outdoor environments. Ideal for accentuating features and creating impactful lighting designs with energy efficiency.

LED

IP65

IK06



PRODUCT SPECIFICATION

LIGHTING FEATURES

| | |
|-------------------------|-----------------------------|
| No. and Type of LED: | 1 pc High Efficacy COB |
| Average LED Life: | 80% after 50000hrs |
| Color Temperature: | 2200K to 5000K / RGB / RGBW |
| CRI: | Ra80+ / Ra90+ |
| Lumen Output at Source: | 65lm/w |
| Total Delivered Lumens: | 620lm / 780lm |

OPTICAL FEATURES

| | |
|--------------|--|
| Beam Angle: | 5° / 15° / 30° / 60° |
| Accessories: | Asymmetric Snoot / Honey comb / Spike / Rod with Spike / Tree Strap / Pole Mounted hoop, base (upon request) |

ELECTRICAL FEATURES

| | |
|-------------------|---|
| Power: | 9W / 12W |
| Voltage: | DC 12V / AC 220V |
| Control Protocol: | On-Off / DMX / Dali / 1-10V / Phase / PWM |

MECHANICAL FEATURES

| | |
|-------------------|---|
| Dimensions: | D64 x H100mm x L145mm |
| Housing Material: | Aluminum Housing / Tempered Glass / SS304 Mounted Bracket |
| Finish: | Black / White / Grey / Customized |
| Mounting Type: | Surface mounted (Ground / Wall) |

GENERAL FEATURES

| | |
|---------------------|--|
| Ingress Protection: | IP 65 |
| Operating Temp: | -35°C to 50°C |
| Impact Resistance: | IK 06 |
| Insulation Class: | Class I / Class III |
| Power Cable: | Include 1m neoprene cable (customizable Lengths) |

DIMENSION DRAWING

