



PRODUCT DESCRIPTION

A stylish LED fixture in elegant customizable finishes black, white, grey, or bespoke designed for discreet wall or ground installation. It includes a flexible power interface suitable for indoor or outdoor settings. Constructed from robust materials, it features IP65-rated protection, ensuring reliability in varied environments. With its thoughtfully simple design, this fixture adapts effortlessly to residential or commercial spaces, blending refined aesthetics with dependable performance.

LED

IP65

IK06



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	1pcs High Efficacy COB
Average LED Life:	80% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	1600lm / 1800lm

OPTICAL FEATURES

Beam Angle:	5° / 15° / 30° / 60°
Accessories:	Asymmetric Snoot / Honey comb / Spike / Rod with Spike / Tree Strap / Pole Mounted Hoop, Base (upon request)

ELECTRICAL FEATURES

Power:	20W / 25W
Voltage:	DC 24V / AC 220V
Control Protocol:	On-Off / DMX / Dali / 1-10V / PWM

MECHANICAL FEATURES

Dimensions:	Φ100 x H185mm x L150mm
Housing Material:	Die-Cast Aluminum Housing / Tempered Glass
Finish:	Black / White / Grey / Customized
Mounting Type:	Surface Mounted (Ground / Wall)

GENERAL FEATURES

Ingress Protection:	IP 65
Operating Temp:	-35°C to 50°C
Impact Resistance:	IK 06
Insulation Class:	Class I / Class III
Power Cable:	Include 1m Neoprene Cable (Customizable lengths)

DIMENSION DRAWING

