



PRODUCT DESCRIPTION

Spot Light AA-SP64 elevates the atmosphere of any space. Designed to highlight and enhance, it brings architectural details, landscaping, or art to life with warm, inviting light. Thoughtfully crafted for both elegance and endurance, it fits seamlessly into indoor and outdoor environments while delivering consistent long-lasting illumination.

LED

IP65

IK06



PRODUCT SPECIFICATION

LIGHTING FEATURES

| | |
|-------------------------|-----------------------------|
| No. and Type of LED: | 1pc High Efficacy COB |
| Average LED Life: | 80% after 50000hrs |
| Color Temperature: | 2200K to 5000K / RGB / RGBW |
| CRI: | Ra80+ / Ra90+ |
| Lumen Output at Source: | 75lm/w |
| Total Delivered Lumens: | 675lm / 920lm |

OPTICAL FEATURES

| | |
|--------------|--|
| Beam Angle: | 5° / 15° / 30° / 60° |
| Accessories: | Asymmetric Snoot / Honey comb / Spike / Rod with Spike / Tree Strap / Pole Mounted Hoop, Base (upon request) |

ELECTRICAL FEATURES

| | |
|-------------------|-----------------------------------|
| Power: | 9W / 12W |
| Voltage: | DC 24V / AC 220V |
| Control Protocol: | On-Off / DMX / Dali / 1-10V / PWM |

MECHANICAL FEATURES

| | |
|-------------------|--|
| Dimensions: | Φ65 x H148 x L115mm |
| Housing Material: | Die-Cast Aluminum Housing / Tempered Glass |
| Finish: | Black / White / Grey / Customized |
| Mounting Type: | Surface Mounted (Ground / Wall) |

GENERAL FEATURES

| | |
|---------------------|--|
| Ingress Protection: | IP 65 |
| Operating Temp: | -35°C to 50°C |
| Impact Resistance: | IK 06 |
| Insulation Class: | Class I / Class III |
| Power Cable: | Include 1m Neoprene Cable (Customizable lengths) |

DIMENSION DRAWING

