



PRODUCT DESCRIPTION

An outdoor architectural spotlight designed to accentuate gardens, façades, or hardscapes. Available in classic black, white, grey, or custom finishes, it mounts discreetly on walls or the ground. Engineered for durability, it withstands harsh weather conditions, ensuring long-lasting performance. Ideal for enhancing outdoor spaces with elegant and reliable illumination.

LED

IP65

IK06



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	1pc High Efficacy COB
Average LED Life:	80% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	240lm / 360lm

OPTICAL FEATURES

Beam Angle:	15° / 24° / 36° / 60°
Accessories:	Honey-comb / Asymmetric Snoot / Spike / Rod with Spike / Tree Strap / Pole Mounted Hoop, Base (upon request)

ELECTRICAL FEATURES

Power:	3W / 5W
Voltage:	DC 24V / AC 220V
Control Protocol:	On-Off / DMX / Dali / 1-10 V / PWM

MECHANICAL FEATURES

Dimensions:	D40mm x H100 x L110mm
Housing Material:	Dia-Cast Aluminum / Tempered Glass
Finish:	Black / White / Grey / Customizable
Mounting Type:	Surface Mounted (Ground / Wall)

GENERAL FEATURES

Ingress Protection:	IP 65
Operating Temp:	From -35°C to + 50°C
Impact Resistance:	IK 06
Insulation Class:	Class I / Class III
Power Cables:	Include 1m Neoprene Cable (customizable lengths)

DIMENSION DRAWING

