



PRODUCT DESCRIPTION

An outdoor architectural spotlight that beautifully accentuates façades, landscapes, or hardscapes with refined elegance. Offered in black, white, grey, or custom finishes, it installs easily on walls or the ground. Built to endure changing conditions, it includes a quality cable and driver. With subtle presence and lasting design, it enhances any outdoor space with tasteful illumination.

LED

IP65

IK06



PRODUCT SPECIFICATION

LIGHTING FEATURES

| | |
|-------------------------|-----------------------------|
| No. and Type of LED: | 1pc High Efficacy COB |
| Average LED Life: | 80% after 50000hrs |
| Color Temperature: | 22000K TO 5000K / RGB /RGBW |
| CRI: | Ra80+ / Ra90+ |
| Lumen Output at Source: | - |
| Total Delivered Lumens: | 725lm / 984lm |

OPTICAL FEATURES

| | |
|--------------|--|
| Beam Angle: | 15° / 24° / 36° / 60° |
| Accessories: | Honey comb / Asymmetric Snoot / Spike / Rod with Spike / Tree Strap / Pole Mounted Hoop, Base / (upon request) |

ELECTRICAL FEATURES

| | |
|-------------------|---------------------------------|
| Power: | 9W / 12W |
| Voltage: | DC 24V / AC 220V |
| Control Protocol: | On-off / DMX /Dali /1-10V / PWM |

MECHANICAL FEATURES

| | |
|-------------------|--|
| Dimensions: | Φ65mm x H160mm x L130mm |
| Housing Material: | Die-Cast Aluminum Housing / Tempered Glass |
| Finish: | Black / White / Grey / Customized |
| Mounting Type: | Surface Mounted (Ground / Wall) |

GENERAL FEATURES

| | |
|---------------------|----------------------|
| Ingress Protection: | IP 65 |
| Operating Temp: | From -35°C to + 50°C |
| Impact Resistance: | IK 06 |
| Insulation Class: | Class I / Class III |

DIMENSION DRAWING

