



PRODUCT DESCRIPTION

A sleek and versatile lighting fixture designed for wall or ground installation, crafted from durable aluminum with customizable finishes for timeless elegance. Choose from warm to cool white tones or vibrant RGB/RGBW lighting to suit your mood or setting. Engineered for consistent, high-quality illumination, it enhances any environment with subtle sophistication.

LED

IP65

IK06



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	16pc High Power LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	2050lm / 2320lm

OPTICAL FEATURES

Beam Angle:	12° / 24° / 38° / 50° / 70*70° / 35*70° / 90*90°
Accessories:	Asymmetric Snoot / Honey comb/ Spike / Tree Strap /Pole Mounted Hoop, Base (upon request)

ELECTRICAL FEATURES

Power:	25W / 30W
Voltage:	DC 24V / AC 220V
Control Protocol:	On-Off / DMX / DALI / 1-10V / PWM

MECHANICAL FEATURES

Dimensions:	L130mm x W188mm x H125mm
Housing Material:	Aluminum Housing / Tempered Glass / SS304 Mounted Bracket
Finish:	Black / White / Grey / Customized
Mounting Type:	Surface Mounted (Ground and Wall)

GENERAL FEATURES

Ingress Protection:	IP 65
Operating Temp:	-35°C to 50°C
Impact Resistance:	IK 06
Insulation Class:	Class I / Class III
Power Cables:	Include 1m Neoprene cable (customizable lengths)

DIMENSION DRAWING

