



PRODUCT DESCRIPTION

A refined surface-mounted spotlight designed to enhance any setting with warm, atmospheric glow. Its sturdy yet stylish build and customizable finishes blend seamlessly into outdoor or indoor scenes. Versatile and elegant, it offers flexible mounting and control options for tailored illumination that elevates ambiance and highlights architectural or landscape features with subtle sophistication.

LED

IP65

IK06



PRODUCT SPECIFICATION

LIGHTING FEATURES

LED Type:	1pc High Power LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	60lm/w , 75lm/w
Total Delivered Lumens:	180lm / 360lm

OPTICAL FEATURES

Beam Angle:	12° / 24° / 38° / 50° / 70*70° / 35*70° / 90*90°
Accessories:	Asymmetric Snoot / Honey comb/ Spike / Tree Strap /Pole Mounted Hoop, Base (upon request)

ELECTRICAL FEATURES

Power:	3W / 5W
Voltage:	DC 24V / AC 220V
Control Protocol:	On-Off / DMX / DALI / 1-10V / PWM

MECHANICAL FEATURES

Dimensions:	L60mm x W98mm x H75mm
Housing Material:	Aluminum Housing / Tempered Glass / SS304 Mounted Bracket
Finish:	Black / White / Grey / Customized
Mounting Type:	Surface Mounted (Ground and Wall)

GENERAL FEATURES

Ingress Protection:	IP 65
Operating Temp:	-35°C to 50°C
Impact Resistance:	IK 06
Insulation Class:	Class I / Class III
Power Cables:	Include 1m Neoprene cable (customizable lengths)

DIMENSION DRAWING

