



PRODUCT DESCRIPTION

An elegantly recessed LED fixture designed for seamless integration into ceilings, walls, or floors with minimal visual presence. Showcased through a sleek stainless steel trim and slender profile, it offers customizable illumination in warm tones or vibrant RGB hues. Built for discreet sophistication, it enhances architectural spaces with refined ambiance while maintaining clean, uninterrupted surfaces, ideal for modern interiors and subtle landscape or guided lighting.

LED

IP67

IK08



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	3pcs SMD LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	420lm

OPTICAL FEATURES

Beam Angle:	Spot 15° / Flood 25° / 40° / 60°
Accessory:	Honey-comb / Louvre / Half-shield / Optics Lens / Frosted (upon request)

ELECTRICAL FEATURES

Power:	6W
Voltage:	DC 24V / AC 220V
Control Protocol:	On-Off / DALI / 1-10 V / DMX / PWM

MECHANICAL FEATURES

Dimensions:	D130mm x H142mm
Housing Material:	SS316 Flange Trim / Black Aluminum Body
Finish:	Steel Brush / Custom Made
Mounting Type:	Recessed (Inground / Wall / Ceiling)

GENERAL FEATURES

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50°C
Impact Resistance:	IK 08
Insulation Class:	Class I / Class III
Cable:	Include 1m Neoprene Cable (customizable lengths)

DIMENSION DRAWING

