



PRODUCT DESCRIPTION

Stylishly designed with a seamless stainless-steel trim and sleek black body, this recessed fixture sits flush in floors, walls, or ceilings to create a clean, integrated look. Perfect for softly highlighting pathways, architectural elements, and outdoor landscaping. Rugged enough to withstand weather and subtle impacts, it offers ambient illumination that enhances spaces without stealing the spotlight.

LED

IP67

IK08



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	2pc SMD LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	52lm/w
Total Delivered Lumens:	210lm

OPTICAL FEATURES

Beam Angle:	Spot 15° / Flood 25° / 40° / 60°
Accessory:	Honey-comb / Louvre / Half-shield / Optics Lens / Frosted (upon request)

ELECTRICAL FEATURES

Power:	4W
Voltage:	DC 24V / AC 220V
Control Protocol:	On-Off / DALI / 1-10 V / DMX / PWM

MECHANICAL FEATURES

Dimensions:	D95mm x H110mm
Housing Material:	SS316 Flange Trim and Black Aluminum Body
Finish:	Steel Brush / Custom Made
Mounting Type:	Recessed (Inground / Wall / Ceiling)

GENERAL FEATURES

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50° C
Impact Resistance:	IK 08
Insulation Class:	Class I / Class III
Cable:	Include 1m Neoprene Cable (customizable lengths)

DIMENSION DRAWING

