



**PRODUCT DESCRIPTION**

A slim, rectangular light bar that sits flush in floors, walls, or ceilings built to blend seamlessly with its surroundings. Housed in cleanly finished aluminum with a clear protective cover, it delivers a smooth, continuous beam of light. It's robust and weather-resistant (IP67), making it ideal for illuminating pathways, accentuating architectural lines, or adding elegant ambiance to indoor and outdoor spaces without drawing attention to the fixture itself.

LED

IP67

IK06



**PRODUCT SPECIFICATION**

**LIGHTING FEATURES**

No. and Type of LED:	24pcs / 48pcs SMD LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	650lm / 1300lm

**OPTICAL FEATURES**

Beam Angle:	10° / 15° / 25° / 30° / 40° / 60°
Accessory:	NA

**ELECTRICAL FEATURES**

Power:	9W / 18W
Voltage:	DC 12V / DC 24V
Control Protocol:	On-Off / DMX / DALI / 1-10 V / PWM

**MECHANICAL FEATURES**

Dimensions:	L500mm / L1000m x W36mm x H31mm
Housing Material:	Aluminum / Tempered Glass
Finish: Mounting	Black / White / Grey / Customized
Type:	Recessed (Ground, Wall, Ceiling)

**GENERAL FEATURES**

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50° C
Impact Resistance:	IK 06
Insulation Class:	Class III
Cable:	Include 1m Neoprene Cable (customizable lengths)

**DIMENSION DRAWING**

