



## PRODUCT DESCRIPTION

A sleek, recessed lighting solution designed to beautifully enhance pathways, outdoor patios, and architectural features. Crafted for durability with a high-quality stainless steel and aluminum housing, this fixture stands tough weather conditions. It offers versatile color options and control modes, making it both practical and visually appealing in a variety of environments.

LED

IP67

IK08



## PRODUCT SPECIFICATION

### LIGHTING FEATURES

No. and Type of LED:	6pc SMD LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	860lm / 980lm

### OPTICAL FEATURES

Beam Angle:	Narrow 10° / Spot 15° / Flood 25° / 40° / 60°
Accessory:	Honey comb / Louvre / Half shield / Optics Lens / Frosted (upon request)

### ELECTRICAL FEATURES

Power:	12W / 15W (Remote Driver / Built in Driver)
Voltage:	DC 12V / DC 24V / AC 220V
Control Protocol:	On-Off / DALI / 1-10 V / DMX / PWM

### MECHANICAL FEATURES

Dimensions:	D150mm x H89mm
Housing Material:	SS316 Flange Trim and Black Aluminum Body
Finish:	Steel Brush / Custom Made
Mounting Type:	Recessed (Inground / Wall / Ceiling)

### GENERAL FEATURES

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50° C
Impact Resistance:	IK 08
Insulation Class:	Class I / Class III
Cable:	Include 1m Neoprene Cable (customizable lengths)

## DIMENSION DRAWING

