



PRODUCT DESCRIPTION

This sleek, recessed LED fixture delivers vibrant, long-lasting light while seamlessly blending into walls, ceilings, or outdoor spaces. Designed for durability and performance, it offers effortless integration into any environment—simply install it once and enjoy years of reliable, maintenance-free illumination.

LED

IP67

IK08



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	9pc SMD LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	1380lm / 1710lm

OPTICAL FEATURES

Beam Angle:	Narrow 8° / Spot 15° / Flood 25° / 40° / 60°
Accessory:	Honey comb / Louvre / Half shield / Optics Lens / Frosted (upon request)

ELECTRICAL FEATURES

Power:	18W / 24W (Remote Driver / Built in Driver)
Voltage:	DC 12V / DC 24V / AC 220V
Control Protocol:	On-Off / DALI / 1-10 V / DMX / PWM

MECHANICAL FEATURES

Dimensions:	D180mm x H97mm
Housing Material:	SS316 Flange Trim and Black Aluminum Body
Finish:	Steel Brush / Custom Made
Mounting Type:	Recessed (Inground / Wall / Ceiling)

GENERAL FEATURES

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50° C
Impact Resistance:	IK 08
Insulation Class:	Class I / Class III
Cable:	Include 1m Neoprene Cable (customizable lengths)

DIMENSION DRAWING

