



## PRODUCT DESCRIPTION

A refined, inground LED uplight that delivers smooth, vibrant illumination with a sleek stainless-steel trim. Built for seamless integration in walls, ceilings, or outdoor spaces, it offers dependable performance even in harsh environments install it once and enjoy long-lasting, maintenance-free lighting.

LED

IP67

IK08



## PRODUCT SPECIFICATION

### LIGHTING FEATURES

No. and Type of LED:	16pc SMD LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	1810lm / 2110lm

### OPTICAL FEATURES

Beam Angle:	Narrow 8° / Spot 15° / Flood 25° / 40° / 60°
Accessory:	Honey comb / Louvre / Half shield / Optics Lens / Frosted (upon request)

### ELECTRICAL FEATURES

Power:	24W / 30W (Remote Driver / Built in Driver)
Voltage:	DC 12V / DC 24V / AC 220V
Control Protocol:	On-Off / DALI / 1-10 V / DMX / PWM

### MECHANICAL FEATURES

Dimensions:	D210mm x H146mm
Housing Material:	SS316 Flange Trim and Black Aluminum Body
Finish:	Steel Brush / Custom Made
Mounting Type:	Recessed (Inground / Wall / Ceiling)

### GENERAL FEATURES

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50° C
Impact Resistance:	IK 08
Insulation Class:	Class I / Class III
Cable:	Include 1m Neoprene Cable (customizable lengths)

## DIMENSION DRAWING

