



PRODUCT DESCRIPTION

An architectural-grade recessed LED fixture seamlessly blends into inground, wall, or ceiling installations with discreet elegance. Its refined aesthetic, accentuated by sleek trimmed apertures, complements minimalist interiors and high-end design schemes. Robust and durable, it's ideal for demanding environments and architectural spaces designed for subtle sophistication.

LED

IP67

IK08



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	18pc SMD LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	2700lm / 2920lm

OPTICAL FEATURES

Beam Angle:	Narrow 8° / Spot 15° / Flood 25° / 40° / 60°
Accessory:	Honey comb / Louvre / Half shield / Optics Lens / Frosted (upon request)

ELECTRICAL FEATURES

Power:	36W / 42W
Voltage:	DC 12V / DC 24V / AC 220V
Control Protocol:	On-Off / DALI / 1-10 V / DMX / PWM

MECHANICAL FEATURES

Dimensions:	D260mm x H167mm
Housing Material:	SS316 Flange Trim / Black Aluminum Body
Finish:	Steel Brush / Custom Made
Mounting Type:	Recessed (Inground / Wall / Ceiling)

GENERAL FEATURES

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50°C
Impact Resistance:	IK 08
Insulation Class:	Class I / Class III
Cable:	Include 1m Neoprene Cable (customizable lengths)

DIMENSION DRAWING

