



PRODUCT DESCRIPTION

A modern LED street-light fixture featuring a slender aluminum housing and smooth PMMA diffuser offers an elegant and refined appearance while delivering clear, evenly distributed illumination. Designed with practical durability in mind, it blends clean geometric lines that suit contemporary outdoor settings. Its understated aesthetic is both purposeful and harmonious, adding functional lighting without overpowering its environment.

LED

IP65

IK05



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. of LED:	-
Average LED Life:	70% after 50000hrs
Color Temperature:	3000K to 6000K
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	3000lm / 5000lm

OPTICAL FEATURES

Beam Angle:	-
Accessory:	NA

ELECTRICAL FEATURES

Power:	30W / 50W
Voltage:	AC 220V (Integrated Driver)
Control Protocol:	On-Off / DALI

MECHANICAL FEATURES

Dimensions:	L550mm x W180mm x H3000mm
Pole Top:	D76mm
Housing Material:	Aluminum / PMMA Diffuser
Finish:	Black RAL9011 / White RAL9003 , RAL9010 / Grey RAL9006 / Custom made
Mounting Type:	Surface Mounted

GENERAL FEATURES

Ingress Protection:	IP 65
Operating Temp:	From -35°C to 50°C
Impact Resistance:	IK 05
Insulation Class:	Class I

DIMENSION DRAWING

