



## PRODUCT DESCRIPTION

A refined outdoor lantern with a sleek, circular top mounted on elegant arm supports and a minimalist post. Its graceful form blends seamlessly into contemporary landscapes, adding a hint of architectural sophistication. Versatile and stylish, it enhances gardens, plazas, and walkways while offering a subtle design statement. Offered in timeless shades like black, white, grey or fully customizable, for lasting visual harmony.

LED

IP65

IK05



## PRODUCT SPECIFICATION

### LIGHTING FEATURES

No. of LED:	-
Average LED Life:	70% after 50000hrs
Color Temperature:	3000K to 6000K
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	3000lm / 5000lm

### OPTICAL FEATURES

Beam Angle:	-
Accessory:	NA

### ELECTRICAL FEATURES

Power:	30W / 50W
Voltage:	AC 220V (Integrated Driver)
Control Protocol:	On-Off / DALI

### MECHANICAL FEATURES

Dimensions:	D880mm x H400mm
Pole Top:	D76mm
Housing Material:	Aluminum / PMMA Diffuser
Finish:	Black RAL9011 / White RAL9003 , RAL9010 / Grey RAL9006 / Custom made
Mounting Type:	Surface Mounted

### GENERAL FEATURES

Ingress Protection:	IP 65
Operating Temp:	From -35°C to 50°C
Impact Resistance:	IK 05
Insulation Class:	Class I

## DIMENSION DRAWING

