



## PRODUCT DESCRIPTION

This AA-FL160 delivers high-performance lighting in a refined, resilient form. Designed for versatility, it combines sleek elegance with robust construction, ready to shine in any setting, indoors or out. With adaptable color options from warm to vivid hues, and an array of beam styles for pinpoint precision or broad coverage, it brings both ambiance and power. Built to last under tough conditions, it's a smart, stylish choice that elevates every environment.

LED

IP66

IK05



## PRODUCT SPECIFICATION

### LIGHTING FEATURES

No. of LED:	30pcs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 6000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	8200lm

### OPTICAL FEATURES

Beam Angle:	5° / 12° / 24° / 38° / 50° / 50*50° / 70*70° / 35*70° / 90*90°
Accessory:	Anti Glare Shield

### ELECTRICAL FEATURES

Power:	100W (Integrated Driver)
Voltage:	AC 220V
Control Protocol:	On-Off / PWM / Phase / 1-10V / Dali / DMX / DMX+RDM

### MECHANICAL FEATURES

Dimensions:	L525mm x W160mm x H220mm
Housing Material:	Aluminum / Tempered Glass / SS304 Bracket
Finish:	Black RAL9011 / White RAL9003 , RAL9010 / Grey RAL9006 / Custom made
Mounting Type:	Surface Mounted

### GENERAL FEATURES

Ingress Protection:	IP 66
Operating Temp:	From -35°C to 50°C
Impact Resistance:	IK 05
Insulation Class:	Class I

## DIMENSION DRAWING

