



PRODUCT DESCRIPTION

This powerful LED light fixture offers versatile color temperatures and customizable beam angles to suit various lighting needs. Designed with durable aluminum housing and tempered glass, it ensures long-lasting performance even in harsh environments. Its sleek finishes blend seamlessly into any setting, while advanced control options allow precise lighting adjustments. Built for reliability and efficiency, this fixture is ideal for both indoor and outdoor use, delivering high-quality illumination with robust protection.

LED

IP66

IK05



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. of LED:	60pcs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 6000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	2 x 8200lm

OPTICAL FEATURES

Beam Angle:	5° / 12° / 24° / 38° / 50° / 50*50° / 70*70° / 35*70° / 90*90°
Accessory:	Anti Glare Shield

ELECTRICAL FEATURES

Power:	200W (Integrated Driver)
Voltage:	AC 220V
Control Protocol:	On-Off / PWM / Phase / 1-10V / Dali / DMX / DMX+RDM

MECHANICAL FEATURES

Dimensions:	L537mm x W360mm x H260mm
Housing Material:	Aluminum / Tempered Glass / SS304 Bracket
Finish:	Black RAL9011 / White RAL9003 , RAL9010 / Grey RAL9006 / Custom made
Mounting Type:	Surface Mounted

GENERAL FEATURES

Ingress Protection:	IP 66
Operating Temp:	From -35°C to 50°C
Impact Resistance:	IK 05
Insulation Class:	Class I

DIMENSION DRAWING

