



PRODUCT DESCRIPTION

An elegant linear LED luminaire, carefully recessed into ceilings, walls or floors to blend seamlessly into contemporary spaces. It offers customizable finishes and color options to suit architectural interiors. Equipped with versatile lighting control, it delivers smooth, uniform illumination that enhances ambiance and feature lines. Durable in challenging environments, it combines resilience and refined aesthetics for both interior and exterior architectural lighting projects.

LED

IP67

IK08



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	12pcs / 24pcs High Power LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	1920lm / 3840lm

OPTICAL FEATURES

Beam Angle:	Narrow 10° / Spot 15° / Flood 25° / 40° / 60°
Accessory:	NA

ELECTRICAL FEATURES

Power:	24W / 48W
Voltage:	DC 12V / DC 24V / AC 220V
Control Protocol:	On-Off / DMX / DALI / 1-10 V / PWM

MECHANICAL FEATURES

Dimensions:	L500mm / L1000m x W81mm x H100mm
Housing Material:	SS316 Flange Trims / Aluminum Body / Tempered Glass
Finish:	Steel Brush
Mounting Type:	Recessed (Ground / Wall / Ceiling)

GENERAL FEATURES

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50°C
Impact Resistance:	IK 08
Insulation Class:	Class I / Class III
Cable:	Include 1m Neoprene Cable (customizable lengths)

DIMENSION DRAWING

