



PRODUCT DESCRIPTION

A gracefully slender pole of subtle presence, this outdoor luminaire casts a soft, focused glow that gently outlines paths and borders. Its minimalist profile blends unobtrusively with contemporary landscapes, imparting a calm, refined rhythm to gardens, walkways, or courtyards. Muted finishes and careful simplicity make it a quietly striking visual element after dusk.

LED

IP66

IK05



Dimmable

PRODUCT SPECIFICATION

LIGHTING FEATURES

No. of LED:	1 x 3pcs / 2 x 3pcs / 3 x 3pcs / 4 x 3pcs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 6000K
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	-

OPTICAL FEATURES

Beam Angle:	Spot 15° / Flood 30° / Flood 60°
Accessory:	NA

ELECTRICAL FEATURES

Power:	1 x 3W / 2 x 3W / 3 x 3W / 4 x 3W
Voltage:	DC 24V
Control Protocol:	On-Off / PWM / Phase / 1-10V / Dali / DMX / DMX+RDM

MECHANICAL FEATURES

Dimensions:	D40mm x H600mm / D40mm x H900mm / D40mm x H1900mm / D40mm x H2700mm
Housing Material:	Aluminum / Tempered Glass
Finish:	Black RAL9011 / White RAL9003, RAL9010 / Grey RAL9006 / Custom made
Mounting Type:	Surface Mounted

GENERAL FEATURES

Ingress Protection:	IP 66
Operating Temp:	From -35°C to 50°C
Impact Resistance:	IK 05
Insulation Class:	Class III

DIMENSION DRAWING

