



PRODUCT DESCRIPTION

Elegant window lighting that blends seamlessly into facades. With sleek, modern finishes and curved optics, it casts a soft, uniform glow around window perimeters. Designed to accentuate architecture at night, it adds both warmth and visual interest to exteriors while maintaining a clean, sophisticated aesthetic.

LED

IP65

IK05



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. LED:	3pcs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 6000K / RGB /RGBW
CRI:	Ra 80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	550lm

OPTICAL FEATURES

Beam Angle:	3 x 300°
Accessories:	NA

ELECTRICAL FEATURES

Power:	6W
Voltage:	DC 24V / AC 220V
Control Protocol:	On-Off / PWM / Phase / 1-10V / Dali / DMX

MECHANICAL FEATURES

Dimensions:	W100 x H98mm
Housing Material:	Aluminum / PMMA Optics
Finish:	Black RAL9011 / White RAL9003, RAL9010 / Grey RAL9006 / Customized
Mounting Type:	Wall Mounted

GENERAL FEATURES

Ingress Protection:	IP 65
Operating Temp:	From -35°C to 50°C
Impact Resistance:	IK 05
Insulation Class:	Class I / Class III

DIMENSION DRAWING

