



PRODUCT DESCRIPTION

This magnetic track light, featuring a durable die-cast aluminum shell with a matte painted surface, offers versatile and modern illumination. Its track head is equipped with a strong magnet, ensuring easy and secure installation, suitable for standard 20mm track and accessories. This linear fixture provides efficient and adaptable lighting, seamlessly integrating into contemporary spaces for both functional and aesthetic applications.

IP54

IK08



CE



PRODUCT SPECIFICATION

LIGHTING FEATURES

Type of LED:	Hight Power LED
Average LED Life:	> 50,000h at 25°C Ambient Temperature
Color Temperature:	3000K / 4000K / 6000K
CRI:	Ra90+
Lumen Output at Source:	93 lm/w
Total Delivered Lumens:	1116 lm / 1674 lm / 3348 lm

OPTICAL FEATURES

Beam Angle:	120°
Accessories:	NA

ELECTRICAL FEATURES

Power:	12W / 18W / 36W
Voltage:	DC 48V (built in constant current driver)
Control Protocol:	On-Off / DALI

MECHANICAL FEATURES

Dimensions:	W22mm x H45mm L304mm / L604mm / L904mm
Housing Material:	Aluminum
Finish:	Black / White
Mounting Type:	Track Installation

GENERAL FEATURES

Ingress Protection:	IP 54
Operating Temp:	From -30C° to +50C°
Impact Resistance:	IK 08
Insulation Class:	Insulation class III

DIMENSION DRAWING

