



PRODUCT DESCRIPTION

This recessed adjustable spotlight is built with a durable cast aluminum body that effectively dissipates heat. It features spring-loaded retention tabs for a secure fit into varying ceiling thicknesses and is certified for direct contact with insulation. The fixture's clean white finish complements its discreet, functional design, making it both robust and effortlessly stylish in any interior setting.

LED

IP43

IK06

CE

PRODUCT SPECIFICATION

LIGHTING FEATURES

| | |
|-------------------------|--------------------------------------|
| Type of LED: | High Power LEDs |
| Average LED Life: | >50,000h at 25°C Ambient Temperature |
| Color Temperature: | 3000K / 4000K / 6000K |
| CRI: | Ra95+ |
| Lumen Output at Source: | 120 lm/w |
| Total Delivered Lumens: | 2560lm |

OPTICAL FEATURES

| | |
|-------------|-----------------------|
| Beam Angle: | 15° / 24° / 36° / 55° |
| Accessory: | NA |

ELECTRICAL FEATURES

| | |
|-------------------|--|
| Power: | 32W (OSRAM driver constant current) |
| Voltage: | AC 220V-240V |
| Control Protocol: | On-Off |

MECHANICAL FEATURES

| | |
|-------------------|-------------------------------|
| Dimensions: | 105mm x 120mm, Cut size: 95mm |
| Housing Material: | Aluminum |
| Finish: | White |
| Mounting Type: | Ceiling Recessed |

GENERAL FEATURES

| | |
|---------------------|--------------------|
| Ingress Protection: | IP 43 |
| Operating Temp: | From -30°C to 50°C |
| Impact Resistance: | IK 06 |
| Insulation Class: | Class III |

DIMENSION DRAWING

