



PRODUCT DESCRIPTION

This recessed adjustable spotlight has a durable cast aluminum housing for efficient heat dissipation, promoting performance and longevity. It features adjustable, spring-loaded retention tabs for easy installation in various ceiling thicknesses and is certified for direct insulation contact. With a sleek white finish and black reflector, it fits seamlessly into different interior styles.

LED

IP43

IK08

CE

PRODUCT SPECIFICATION

LIGHTING FEATURES

Type of LED:	Cree Cmu Cro 9 Series
Average LED Life:	>50,000h at 25°C Ambient Temperature
Color Temperature:	3000K
CRI:	Ra95+
Lumen Output at Source:	160 lm/w
Delivered Efficiency:	128 lm/w
Total Delivered Lumens:	4096 lm

OPTICAL FEATURES

Beam Angle:	15° / 24° / 36° / 50°
Accessory:	NA

ELECTRICAL FEATURES

Power:	32W (OSRAM driver constant current)
Voltage:	AC 220V-240V
Control Protocol:	On-Off / DALI

MECHANICAL FEATURES

Dimensions:	115mm x 125mm, Cut size: 95mm
Housing Material:	Aluminum
Finish:	White
Reflector Finish:	Black
Mounting Type:	Ceiling Recessed

GENERAL FEATURES

Ingress Protection:	IP 43
Operating Temp:	From -30°C to 50°C
Impact Resistance:	IK 08
Insulation Class:	Class III

DIMENSION DRAWING

