



PRODUCT DESCRIPTION

This recessed adjustable spotlight features a durable cast aluminum body that efficiently channels away heat. Spring-loaded retention tabs ensure a secure and straightforward ceiling installation, even across varying thicknesses. Designed for direct insulation contact, it delivers safe, compact integration. With its crisp white finish, this fixture balances form and functionality, seamlessly blending into diverse interior aesthetics.

LED

IP43

IK03

CE

PRODUCT SPECIFICATION

LIGHTING FEATURES

Type of LED:	High Power LEDs
Average LED Life:	>50,000h at 25°C Ambient Temperature
Color Temperature:	3000K / 4000K / 6000K
CRI:	Ra95+
Lumen Output at Source:	120 lm/w
Total Delivered Lumens:	3200lm

OPTICAL FEATURES

Beam Angle:	15° / 24° / 36°
Accessory:	NA

ELECTRICAL FEATURES

Power:	32W (OSRAM driver constant current)
Voltage:	AC 220V-240V
Control Protocol:	On-Off

MECHANICAL FEATURES

Dimensions:	135mm x 115mm, Cut size: 120mm
Housing Material:	Aluminum
Finish:	White / Black
Mounting Type:	Ceiling Recessed

GENERAL FEATURES

Ingress Protection:	IP 43
Operating Temp:	From -30°C to 50°C
Impact Resistance:	IK 03
Insulation Class:	Class III

DIMENSION DRAWING

