



PRODUCT DESCRIPTION

The AA-AL4570 is a high-quality linear LED luminaire ideal for grazing and washing building facades. It features an extruded aluminum housing for effective heat dissipation and a custom powder coating that blends well with architecture. Available in various optics and color temperatures, it offers easy installation and connection, making it an excellent choice for enhancing building exteriors.

LED

IP66

IK05

CE

PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	24pcs High Power Bridgelux SMD LEDs
Average LED Life:	80% after 50000hrs
Color Temperature:	Warm White 3000K
CRI:	Ra90+
Lumen Output at Source:	4860 lm
Total Delivered Lumens:	3820 lm

OPTICAL FEATURES

Beam Angle:	Narrow Beam 12°
Accessory:	Honey-comb(upon request)

ELECTRICAL FEATURES

Power:	40W
Voltage:	AC 220V (included driver)
Control Protocol:	ON - OFF

MECHANICAL FEATURES

Dimensions:	L1000mm x W45mm x H70mm
Housing Material:	Extruded Aluminum Body
Finish:	Powder Coating Black, customized
Screen Material:	4mm tempered glass
Mounting Type:	Ceiling Recessed

GENERAL FEATURES

Ingress Protection:	IP 66
Operating Temp:	From -20°C to 50°C
Impact Resistance:	IK05
Insulation Class:	Class I

DIMENSION DRAWING

