



PRODUCT DESCRIPTION

This in-ground light boasts a body made of aluminum, shaped like a short cylinder with subtle ridges that boost its durability for outdoor environments. The SS316 metal trim contributes a modern, stylish touch, while the glass surface provides a sleek and polished finish at the front.

LED

IP67

IK08



PRODUCT SPECIFICATION

LIGHTING FEATURES

No. and Type of LED:	1pc High Power LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 6000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	240lm / 420lm

OPTICAL FEATURES

Beam Angle:	Spot 15° / Flood 25° / 12° / 40° / 60°
Accessory:	NA

ELECTRICAL FEATURES

Power:	3W / 6W
Voltage:	DC 24V / AC 220V
Control Protocol:	ON-OFF / DALI / 1-10 V / DMX / PWM / Phase

MECHANICAL FEATURES

Dimensions:	Dia100mm x H100mm
Housing Material:	Aluminum Housing SS316 Flange Trim and Tempered Glass
Finish:	Black Housing and Brush Flange Trim
Mounting Type:	Recessed

GENERAL FEATURES

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50° C
Impact Resistance:	IK 08
Insulation Class:	Class I / Class III

DIMENSION DRAWING

