



## PRODUCT DESCRIPTION

A sleek and robust in-ground fixture designed to enhance both indoor and outdoor spaces, from gardens and walkways to architectural accents. Crafted with premium stainless steel and aluminum, it's built to withstand the elements and deliver beautiful, long lasting illumination. Offering a variety of color options and control modes, this light is the perfect blend of reliability and ambiance.

LED

IP67

IK08



## PRODUCT SPECIFICATION

### LIGHTING FEATURES

No. and Type of LED:	1pc COB LEDs
Average LED Life:	70% after 50000hrs
Color Temperature:	2200K to 5000K / RGB / RGBW
CRI:	Ra80+ / Ra90+
Lumen Output at Source:	-
Total Delivered Lumens:	510lm / 630lm

### OPTICAL FEATURES

Beam Angle:	Narrow 10° / Spot 15° / Flood 25° / 40° / 60°
Accessory:	Honey comb / Louvre / Half shield / Optics Lens / Frosted (upon request)

### ELECTRICAL FEATURES

Power:	7W / 9W (Remote Driver / Built in Driver)
Voltage:	DC 12V / DC 24V / AC 220V
Control Protocol:	On-Off / DALI / 1-10 V / DMX / PWM

### MECHANICAL FEATURES

Dimensions:	D80mm x H92mm
Housing Material:	SS316 Flange Trim and Black Aluminum Body
Finish:	Steel Brush / Custom Made
Mounting Type:	Recessed (Inground / Wall / Ceiling)

### GENERAL FEATURES

Ingress Protection:	IP 67
Operating Temp:	From -35°C to 50° C
Impact Resistance:	IK 08
Insulation Class:	Class I / Class III
Cable:	Include 1m Neoprene Cable (customizable lengths)

## DIMENSION DRAWING

